

ARCHITECTURAL

GRATES + DRAINS



65TRTDi Threshold with Sub-Sill

The 65TRTDi is a Threshold Drain for door track with sub sill tray featuring our 65mm wide standard grate.

For sliding and Hinged doors.

Featuring a linear stainless steel grate with concealed channel section connecting sill and sub-sill for door tracks and thresholds.


Allows door sills to be drained while having internal and external floor surfaces with no step down.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

SPECIFICATIONS + DIMENSIONS

- Channel Width Channel Depth Length(s) Outlet Size
- 70mm Adjustable As Required N/A

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Aged / Health Care Drainage Balcony Drainage Commercial Drainage Courtyard / Patio Drainage Multi-Residential Drainage Special Needs Drainage **Threshold Drainage**




Visit **stormtech.com.au** for tools + inspiration.

Copyright ☺ Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 17/09/2025 (please check for updates)



Code 65TRTDi Range Threshold Grate Style TR Category Made-to-Length Channel Material Stainless Steel Steel Grade 316



Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.