

ARCHITECTURAL **GRATES + DRAINS**

Code 65PPSTDi

Range Threshold Grate Style PPS

Steel Grade 316

dimensions

Category Made-to-Length

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts

3000mm supplied in sections with joiner. +/-2mm tolerance on

longer than 1200mm supplied in sections. Channels over



65PPSTDi **Threshold with Sub-Sill**

The 65PPSTDi is a Threshold Drain for door track with sub sill tray featuring our 65mm wide **Punched Slot grate.**

For sliding and Hinged doors.

Featuring a linear stainless steel grate with concealed channel section connecting sill and sub-sill for door tracks and thresholds. Allows door sills to be drained while having internal and external floor surfaces with no step down.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

SPECIFICATIONS + DIMENSIONS

Outlet Size

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Multi-Residential Drainage Special Needs Drainage Threshold Drainage

Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 17/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

Channel Width **Channel Depth** Length(s)

75mm Adjustable As Required N/A

