Order and Quote Form

Standard Threshold - With Sill Only



MR-F-8.5.1-R1

Stormtech

TR Standard Wedgewire Grate



Grate Width

O/A Width = 111mm + Door Track Width

Channel + Door Track Dimensions



Length + Outlet Requirements

Please include drainage length and all required outlets.

Overall Length DOOR TRACK SPACE outlet offsel outlet position mm mm, mm,

Pequired Outlet Size

Required Outlet Size				
65 & 100mm Grates	32mm	38mm	44mm	51mm
100mm Grates only	63mm	76mm	89mm	
Optional Compor	nents (Addit	tional Charge	es Apply)	

Concrete Ties (17mm wide / 10mm hole, extend 30mm from base)

Stainless Steel Packer (5mm Thickness)

Electropolishing (recommended for installation in marine or pool area environments)

Overflow Outlet

PLEASE NOTE Minimum channel length equals door track length plus 6mm. Grates longer than 1500mm and Tile Inserts longer than 1200mm are supplied in multiple sections. Channels 2950mm maximum in one piece, channels over 2950mm are supplied in multiple sections with joiner. See AS3500 standard & local regulator for specific outlet & drainage requirements.

+/- 2mm tolerance on dimensions.

Full Name **Email Address** Company Name Order Number Stormtech Quote Number Telephone Signature

stormtech.com.au